

Safety Data Sheet

Issue date 30-Mar-2016 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

BAYBERRY

Chemical name 7-8162

Other means of identification

Product code FG 438-5173-6 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Aerosol

Odor Perfumed

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

_

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical FamilyMIXTURES.Formula7-8162

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

Inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

Ingestion Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsUse with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content	TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

label directions for correct use of the product...

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor

Color Will vary depending on the Odor threshold No information available

Perfumed.

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

Melting point/freezing point

Boiling point/boiling range
Flash Point

Not applicable

No information available

Acetone 133 F/56.29 C

This is an aerosol product for which

No information available

No information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableRelative Density0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information available

Solubility in other solvents
Partition coefficient
Autoignition Temperature
Decomposition temperature
No information available
No information available
No information available
No information available

Kinematic viscosity

No information available

Pynamic viscosity

No information available

Explosive properties No information available Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

VOC content (%) 29.63 **Density** 7.16 lb/gal

Bulk Density No information available

10. Stability and Reactivity

Reactivity

Not applicable No data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

Inhalation No data available.

Eye Contact No data available.

Skin contact No data available.

Ingestion No data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 4200 μL/kg(Rabbit)= 6 mL/kg(Rat)	> 5240 mg/m³(Rat)4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity -

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L	EC50 = 14500 mg/L 15 min	12600 - 12700: 48 h Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		10294 - 17704: 48 h
		macrochirus mg/L LC50		Daphnia magna mg/L EC50
		6210 - 8120: 96 h		Static
		Pimephales promelas mg/L LC50 static		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 13400: 96 h Salmo		
		gairdneri mg/L LC50 flow-through 19100 - 23900:		
		96 h Lepomis macrochirus		
		mg/L LC50 flow-through		
		11400 - 15700: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 flow-through 11600 -		
		16700: 96 h Pimephales		
		promelas mg/L LC50 flow-through		
Petroleum distillates,		2.2: 96 h Lepomis		4720: 96 h Den-dronereides
hydrotreated light		macrochirus mg/L LC50		heteropoda mg/L LC50
64742-47-8		static 45: 96 h Pimephales		neteropoda mg/E 2000
		promelas mg/L LC50		
		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone	-0.24
67-64-1	
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes

Dispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity

Hazard Class ORM-D

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	X	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	Х	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
HMIS_	Health Hazards 2	Flammability 4	Physical hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 30-Mar-2016

Revision note

This SDS supersedes a previous MSDS dated March 13, 2013.

<u>Disclaimer</u>

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 28-Apr-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

OCEAN MIST

Chemical name 7-8163

Other means of identification

Product code FG 438-5178-7GHS Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol
aerosolized.

Odor Perfumed.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical Family MIXTURES. Formula 7-8163

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color will vary depending on the Odor threshold No information available

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits
Lower Flammability Limit
Not available
Not available

Vapor pressure

No information available

No information available

No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solvents

Partition coefficient

Autoignition Temperature

Decomposition temperature

Kinematic viscosity

No information available

Dynamic viscosity No information available

Oxidizing properties No information available

No information available

Other Information

Softening point No information available Molecular weight No information available

VOC content (%) 29.63 **Density** 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalation no data available.

Eye Contact no data available.

Skin contact no data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 28-Apr-2015

Revision note

This SDS supersedes a previous SDS dated December 19, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 07-Jan-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER POWDER FRESH

Chemical name 7-8169

Other means of identification

Product code FG 438-5185-6 GHS Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Aerosol

Odor Perfumed.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

_

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical FamilyMIXTURES.Formula7-8169

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsUse with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor

Color Color will vary depending on the Odor threshold No information available

Perfumed.

perfume in the product.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

This is an aerosol product for which Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information available

Solubility in other solvents
Partition coefficient
Autoignition Temperature
No information available

Kinematic viscosity

Dynamic viscosity

No information available
No information available

Explosive propertiesNo information available **Oxidizing properties**No information available

Other Information

Softening point No information available

Molecular weight No information available

VOC content (%) 29.63 **Density** 7.16 lb/gal

Bulk Density No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 120 F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 120 F.

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalation no data available.

Eye Contact no data available.

Skin contact no data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³(Rat)4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h
67-64-1		Pimephales promelas mg/L	3	Daphnia magna mg/L EC50
		LC50 static 4.74 - 6.33: 96 h		Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packagingPressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	Х	X	
Propane 74-98-6	Х	X	Х

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information					
<u>NFPA</u>	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable	
HMIS	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection	

Prepared by Regulatory Department

Issue date 07-Jan-2015

Revision note

This SDS supersedes a previous SDS dated August 01, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 27-Oct-2015 Version 2

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

ODOR NEUTRALIZER

Chemical name 7-8170-1

Other means of identification

Product code FG 438-5186-8 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised against Do not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED Causes serious eye irritation May cause drowsiness or dizziness EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Aerosol

Odor Perfumed.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- · Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical FamilyMIXTURES.Formula7-8170-1

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

Inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

Ingestion Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

label directions for correct use of the product..

Wash hands thoroughly after handling. General hygiene considerations

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor

Color Color will vary depending on the

perfume in the product.

Perfumed. Odor threshold

No information available

Property <u>Values</u> Remarks • Method

Not applicable Solvent-based product. На Melting point/freezing point Not applicable No information available Boiling point/boiling range Acetone 133 F/56.29 C No information available **Flash Point** This is an aerosol product for which No information available

> Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Faster than butyl acetate

No information available No information available

No information available

Upper flammability limits Not available

Lower Flammability Limit Not available

Vapor pressure No information available **Vapor Density** No information available

Relative Density 0.86 g/ml No information available Water solubility Insoluble in water No information available

Solubility in other solvents No information available Partition coefficient No information available **Autoignition Temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available

Dynamic viscosity No information available

Explosive properties No information available **Oxidizing properties** No information available

Other Information

Evaporation Rate Flammability (solid, gas)

Flammability Limits in Air

No information available Softening point Molecular weight No information available

VOC content (%) 29.63 **Density** 7.16 lb/gal

No information available **Bulk Density**

10. Stability and Reactivity

Reactivity

Not applicable No data available

Chemical stability

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

Inhalation No data available.

Eye Contact No data available.

Skin contact No data available.

Ingestion No data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³(Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ cell mutagenicityNo information available.

Carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Acetone		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h
67-64-1		Pimephales promelas mg/L	_	Daphnia magna mg/L EC50
		LC50 static 4.74 - 6.33: 96 h		Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity

Hazard Class ORM-D

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	X		Х
N-Butane 106-97-8	X	X	Х
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	Х	X	Х

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information							
NFPA	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable			
HMIS	Health Hazards 2	Flammability 4	Physical hazards 1	Personal Protection B - Eyes and hands protection			

Prepared by Regulatory Department

Issue date 27-Oct-2015

Revision note

This SDS supersedes a previous SDS dated January 20, 2015.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 14-May-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

EXOTIC GARDEN

Chemical name 7-8171

Other means of identification

Product code FG 438-5187-6 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Odor Perfumed. Appearance Clear liquid that will be Physical State Aerosol aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- · Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

3. Composition/information on Ingredients

Metered Air Freshener. **Synonyms**

Chemical Family MIXTURES. **Formula** 7-8171

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color will vary depending on the Odor threshold No information available

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

Melting point/freezing point

Boiling point/boiling range
Flash Point

Not applicable
Not applicable
No information available
Acetone 133 F/56.29 C
This is an aerosol product for which
No information available
No information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits
Lower Flammability Limit
Not available
Not available

Vapor pressure

No information available

No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Explosive properties

No information available

Oxidizing properties

No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalationno data available.Eye Contactno data available.Skin contactno data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

	Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Γ	Acetone		Included in waste stream:		U002
	67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 14-May-2015

Revision note

This SDS supersedes a previous SDS dated August 01, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 23-Mar-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

CINNAMON STICK

Chemical name 7-8175

Other means of identification

Product code FG 438-5190-6 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol Odor Perfumed. aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical Family MIXTURES. Formula 7-8175

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
N-Butane 106-97-8	STEL: 1000 ppm	other sectors (vacated) STEL: 1000 ppm (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	TWA: 800 ppm TWA: 1900 mg/m³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color will vary depending on the Odor threshold No information available

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

Melting point/freezing point

Boiling point/boiling range
Flash Point

Not applicable
Acetone 133 F/56.29 C
This is an aerosol product for which
No information available
No information available
No information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits
Lower Flammability Limit
Not available
Not available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Explosive properties No information available Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product Information This product has not been tested as whole. See below for information on ingredients.

inhalation no data available. no data available. **Eye Contact** no data available. Skin contact

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, **Symptoms**

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin. Irritating to eyes.

Serious eye damage/eye irritation

irritation May cause skin and eye irritation.

corrosivity Not applicable.

No information available. sensitization **Germ Cell Mutagenicity** No information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

No information available. **Reproductive Toxicity** STOT - single exposure No information available. STOT - repeated exposure No information available. **Aspiration Hazard** No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4755 mg/kg ATEmix (dermal) 31248 mg/kg ATEmix (inhalation-gas) 10804 mg/l ATEmix (inhalation-dust/mist) 15 mg/l ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 23-Mar-2015

Revision note

This SDS supersedes a previous SDS dated September 29, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 20-Jan-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

VANILLA BEAN

Chemical name 7-8173

Other means of identification

Product code FG 438-5191-6 **Synonyms** Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised against Do not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-273-1121

Manufacturer Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Aerosol

Odor Perfumed.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- · Harmful to aquatic life with long lasting effects
- Harmful to aquatic life

_

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical FamilyMIXTURES.Formula7-8173

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders

Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor

Color Will vary depending on the Odor threshold No information available

Perfumed.

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based production

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

Flash Point

This is an aerosol product for which Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

Flammability Limits in Air

No information available
No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information available

Kinematic viscosity

Dynamic viscosity

No information available
No information available

Explosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening point No information available Molecular weight No information available

VOC content (%) 29.63 **Density** 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 120 F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 120 F.

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalation no data available.

Eye Contact no data available.

Skin contact no data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³(Rat)4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitization No information available.

Germ Cell Mutagenicity No information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Acetone		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h
67-64-1		Pimephales promelas mg/L		Daphnia magna mg/L EC50
		LC50 static 4.74 - 6.33: 96 h		Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		, ,
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	Х
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	Х	X	
Propane 74-98-6	Х	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

	16. Other information					
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable		
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection		

Prepared by Regulatory Department

Issue date 20-Jan-2015

Revision note

This SDS supersedes a previous SDS dated September 11, 2014.

Disclaime

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 10-Jun-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

CUCUMBER MELON

Chemical name 7-8178

Other means of identification

Product code FG 438-5305-3 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol Odor Perfumed. aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

-

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical Family MIXTURES. Formula 7-8178

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m³ (vacated) STEL: 2400 mg/m³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³
N-Butane 106-97-8	STEL: 1000 ppm	other sectors (vacated) STEL: 1000 ppm (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m³	TWA: 800 ppm TWA: 1900 mg/m³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color will vary depending on the Odor threshold No information available

perfume in the product.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableRelative Density0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information availableNo information available

Explosive properties

No information available

Oxidizing properties

No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalation no data available.Eye Contact no data available.

Skin contact no data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

	Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Γ	Acetone		Included in waste stream:		U002
	67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	Х
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	Х	X	
Propane 74-98-6	Х	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 10-Jun-2015

Revision note

This SDS supersedes a previous SDS dated September 29, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 14-May-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

REFRESHING SPA

Chemical name 7-8179

Other means of identification

Product code FG 438-5306-3 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised against Do not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol Odor Perfumed. aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

-

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical Family MIXTURES. Formula 7-8179

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	· ·

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color will vary depending on the Odor threshold No information available

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

Melting point/freezing point

Boiling point/boiling range
Flash Point

Not applicable
Acetone 133 F/56.29 C
This is an aerosol product for which
No information available
No information available
No information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limitsNot availableLower Flammability LimitNot available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Explosive properties

No information available

Oxidizing properties

No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalationno data available.Eye Contactno data available.Skin contactno data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

	Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Γ	Acetone		Included in waste stream:		U002
	67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	X	X	X
1,1-Difluoroethane 75-37-6	Х	X	
Propane 74-98-6	Х	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 14-May-2015

Revision note

This SDS supersedes a previous MSDS dated January 11, 2013.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 16-Dec-2014 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER WARM HARVEST

Chemical name 7-8181

Other means of identification

Product code FG 438-5310-5 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be aerosolized.

Physical State Aerosol

Odor Perfumed

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

_

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical FamilyMIXTURES.Formula7-8169

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsUse with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color Color will vary depending on the Odor threshold No information available

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information available

Solubility in other solvents
Partition coefficient
Autoignition Temperature
Decomposition temperature
No information available
No information available
No information available
No information available

Kinematic viscosity

No information available

Pynamic viscosity

No information available

Explosive properties

No information available

Oxidizing properties

No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 120 F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 120 F.

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalation no data available.

Eye Contact no data available.

Skin contact no data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³(Rat)4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Diethylene Glycol Monoethyl Ether 111-90-0		10000: 96 h Lepomis macrochirus mg/L LC50 static 19100 - 23900: 96 h Lepomis macrochirus mg/L LC50 flow-through 11400 - 15700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 11600 - 16700: 96 h Pimephales promelas mg/L LC50 flow-through 13400: 96 h Salmo gairdneri mg/L LC50 flow-through		3940 - 4670: 48 h Daphnia magna mg/L EC50
Petroleum distillates, hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 2.2: 96 h Lepomis macrochirus mg/L LC50 static		4720: 96 h Den-dronereides heteropoda mg/L LC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes Dispose of in accordance with federal, state and local regulations.

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate Contaminated packaging container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	Х
Diethylene Glycol Monoethyl Ether 111-90-0	Х		Х
N-Butane 106-97-8	Х	X	Х
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	Х

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
<u>NFPA</u>	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 16-Dec-2014

Revision note

This SDS supersedes a previous MSDS dated January 11, 2013.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 31-Mar-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

SPRING LINEN

Chemical name 7-8185

Other means of identification

Product code FG 438-5318-4 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised againstDo not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol Odor Perfumed. aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

-

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical Family MIXTURES. Formula 7-8185

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	· ·

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color will vary depending on the Odor threshold No information available

perfume in the product.

PropertyValuesRemarks • MethodpHNot applicableSolvent-based product.

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

h Point

This is an aerosol product for which
Flame Projection is 12-14 inches
without flashback. Temperatures
above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limitsNot availableLower Flammability LimitNot available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Explosive properties

No information available

Oxidizing properties

No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalationno data available.Eye Contactno data available.Skin contactno data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 31-Mar-2015

Revision note

This SDS supersedes a previous MSDS dated December 20, 2012.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue date 10-Jun-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON SPRAY SCENTS METERED AIR FRESHENER/DEODORIZER

MOUNTAIN MEADOW

Chemical name 7-8182-1

Other means of identification

Product code FG 438-5311-5 Synonyms Metered Air Freshener

Recommended use of the chemical and restrictions on use

Recommended Use Room Deodorizer.

Uses advised against Do not spray on varnished, painted or plastic surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

HARMFUL IF INHALED
Causes serious eye irritation
May cause drowsiness or dizziness
EXTREMELY FLAMMABLE AEROSOL

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be Physical State Aerosol Odor Perfumed. aerosolized.

Precautionary Statements - Prevention

Avoid breathing fumes, mist, vapors or spray.

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves, protective clothing, eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- MAY BE HARMFUL IF SWALLOWED
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

3. Composition/information on Ingredients

Synonyms Metered Air Freshener.

Chemical Family MIXTURES. Formula 7-8182-1

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	25-30	*
Diethylene Glycol Monoethyl Ether	111-90-0	20-25	*
N-Butane	106-97-8	15-20	*
1,1-Difluoroethane	75-37-6	10-15	*
Propane	74-98-6	5-10	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

FIRST AID MEASURES

Eye Contact

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin contact In case of contact, immediately flush skin with plenty of water. Wash skin with soap and

water. If irritation develops, consult a physician.

inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

INGESTION Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates.

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric

acid and carbonyl halides.

Explosion data

Sensitivity to Mechanical Impact Contents are under pressure. Handle an extremely flammable material. Follow label

directions for correct installation and placement of dispenser. Store cans in a cool, dry place

away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle as an extremely flammable material. Follow label directions for correct installation

and placement of dispenser. Store cans in a cool, dry place away from heat and open

flame.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves.

Respiratory protection Use in a well-ventilated area ONLY. None required if used in a well-ventilated area. Follow

label directions for correct use of the product..

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

ColorColor will vary depending on the **Odor threshold**No information available perfume in the product.

Remarks • Method

Property Values

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeAcetone 133 F/56.29 CNo information availableFlash PointThis is an aerosol product for whichNo information available

Flame Projection is 12-14 inches without flashback. Temperatures above 120 F may cause cans to burst.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits Not available Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableRelative Density0.86 g/mlNo information availableWater solubilityInsoluble in waterNo information availableSolubility in other solventsNo information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information available

Explosive properties

No information available

No information available

Other Information

Softening point No information available Molecular weight No information available

 VOC content (%)
 29.63

 Density
 7.16 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable no data available

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrofluoric acid and carbonyl halides.

11. Toxicological Information

Information on likely routes of exposure

Product InformationThis product has not been tested as whole. See below for information on ingredients.

inhalationno data available.Eye Contactno data available.Skin contactno data available.

INGESTION no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
Diethylene Glycol Monoethyl Ether 111-90-0	= 1920 mg/kg (Rat)	= 6 mL/kg(Rat)= 4200 μL/kg(Rabbit)	> 5240 mg/m³ (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

corrosivity Not applicable.

sensitizationNo information available.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4755 mg/kg
ATEmix (dermal) 31248 mg/kg
ATEmix (inhalation-gas) 10804 mg/l
ATEmix (inhalation-dust/mist) 15 mg/l
ATEmix (inhalation-vapor) 78 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

43.63% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	
67-64-1		Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h		Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h
		Oncorhynchus mykiss mL/L		Daphnia magna mg/L EC50
		LC50 8300: 96 h Lepomis		Daprillia magna mg/L LC30
		macrochirus mg/L LC50		
Diethylene Glycol Monoethyl		10000: 96 h Lepomis		3940 - 4670: 48 h Daphnia
Ether		macrochirus mg/L LC50		magna mg/L EC50
111-90-0		static 19100 - 23900: 96 h		g
		Lepomis macrochirus mg/L		
		LC50 flow-through 11400 -		
		15700: 96 h Oncorhynchus		
		mykiss mg/L LC50		
		flow-through 11600 - 16700:		
		96 h Pimephales promelas		
		mg/L LC50 flow-through		
		13400: 96 h Salmo gairdneri		
		mg/L LC50 flow-through		
Petroleum distillates,		45: 96 h Pimephales		4720: 96 h Den-dronereides
hydrotreated light		promelas mg/L LC50		heteropoda mg/L LC50
64742-47-8		flow-through 2.4: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50 static 2.2: 96 h		
		Lepomis macrochirus mg/L		
		LC50 static		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Diethylene Glycol Monoethyl Ether 111-90-0	-0.8
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastesDispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status
---------------	-----------------------------------

Acetone 67-64-1	Ignitable

14. Transport Information

DOT Limited Quantity - Metered Air Freshener

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Diethylene Glycol Monoethyl Ether - 111-90-0	111-90-0	20-25	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	Х	X	X
Diethylene Glycol Monoethyl Ether 111-90-0	Х		X
N-Butane 106-97-8	Х	X	X
1,1-Difluoroethane 75-37-6	X	X	
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 10-Jun-2015

Revision note

This SDS supersedes a previous MSDS dated April 15, 2013.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet